








	SYMBOL	REVISION	APPROVAL	DATE



RECOMMENDED PCB LAYOUT

TOP VIEW (.XX ± 0.05)



接触点（材质）：磷铜，触点镀金3U"

SPECIFICATIONS

1. ELECTRICAL CHARACTERISTICS:
 - 1-1. RATING: DC 12V 1A
 - 1-2. CONTACT RESISTANCE: 30mΩ MAX (INITIAL)
 - 1-3. DIELECTRIC WITHSTANDING VOLTAGE:
500V AC FOR ONE MINUTE
 - 1-4. INSULATION RESISTANCE: 500MΩ MIN,
MEASURED BY 500V DC
2. LIFE TEST: MECHANICAL LIFE TEST 5,000 CYCLES.
3. TEMPERATURE RISE : 30° C MAX

PART NO.	DIM A	DIM B
QP-2P-1. 27PH-2	2. 54	1. 27
QP-3P-1. 27PH-2	3. 81	
QP-4P-1. 27PH-2	5. 08	2. 54
QP-5P-1. 27PH-2	6. 35	3. 81
QP-6P-1. 27PH-2	7. 62	5. 08
QP-7P-1. 27PH-2	8. 89	6. 35

No.	DESCRIPTION	MATERIAL	PLATING
1	CONTACT TERMINAL	PHOSPHOR COPPER	Au PLATED
2	HOUSING	LCP	BLACK



东莞市轻平电子科技有限公司
DONGGUAN QINGPING ELECTRONIC TECHNOLOGY CO., LTD.

COPYRIGHT RESERVED,PLEASE DO NOT COPY.

PART NAME		CONNECTOR		DRAWING	C.N.Li	DWG.No.	CL0083
PART NO.		SEE "LABEL"		CHECK	G.G.Feng	REV.	A0
	UNIT :	TOLERANCE UNLESS OTHERWISE SPECIFIED X.X ± 0.3 X.XX ± 0.2 X.XXX ± 0.1	ANGLE	APPROVAL	z.y.Cai	DATE	2023-4-15
	mm		0°±3'	SCALE	1:1	PAGE	1 OF 1